



McCormick, Paulding & Huber LLP

Intellectual Property Law

FAX RECEIVED

MAY 13 2002

GROUP 3600

UNOFFICIAL

Offices in
Hartford, CT and
Springfield, MA

DATE: MAY 13, 2002

Tel 860 549.5290
Fax 860 527.0464

CityPlace II
185 Asylum Street
Hartford, CT
06103-3402
www.ip-lawyers.com

FACSIMILE TRANSMISSION

DELIVER TO: Benjamin Pezzello ANT Unil 3613FAX NO: 703-308-3519SENT BY: Bill Gowanlock

TRANSMISSION COMPLETED BY: _____

NO. OF PAGES INCLUDING COVER SHEET: 3OUR REF. NO: 6350-05 YOUR REF. NO: 09/407,053

MESSAGE: _____

Please call.See

John C. Linderman**
J. Kevin Grogan**
Arthur F. Dionne**
Richard R. Michaud*
Marina F. Cunningham*
Daniel G. Mackas*
Susan C. Oygard*
Nicholas J. Tuccillo*
Wm. Tucker Griffith*
Stephen P. Scuderi**
Richard D. Getz*
William B. Gowanlock*
Donald J. MacDonald*
Shirley S. Ma*
Gerald J. Stanton*
*Admitted in CT
**Admitted in MA

Of Counsel

Donald K. Huber*
Frederick J. Haesche*
John C. Hilton*
Charles E. Sohl*
John J. Dempsey

The information contained in this facsimile may contain confidential information. It is only for the use of the individual or entity named. If you are not the intended recipient, or the employee or agent responsible to deliver it to the intended recipient, you are notified that your dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please immediately notify us by telephone, and return the original message to us at the above address via U.S. postal service.

DO NOT ENTER

REJECTION - §103(a) CARLSTON IN VIEW OF MAGOWAN IN VIEW OF
PLATKIEWICZ AND FURTHER IN VIEW OF CURTIS AND SPENCER

Claim 1

1. (Five Times Amended) A bearing pad assembly comprising:
 - a first housing having an exterior surface and defining a bore extending at least part-way through said first housing;
 - a first load bearing member coupled to said first housing, and defining an outwardly facing first abutment surface;
 - a second housing defining a bore of a shape similar to said exterior surface of said first housing and adapted to slideably receive said first housing therein;
 - a second load bearing member coupled to said second housing and defining an outwardly facing second abutment surface opposite to said first abutment surface;
 - at least one slip lining positioned between said first housing exterior surface and a bore wall defining said second housing bore; and
 - at least one compression spring positioned within said first housing bore, wherein said compression spring [comprises a solid resilient material] having a [torus] toroidal shape, the toroid having an outside diameter minus an inside diameter equal to or greater than a height when positioned in the bearing pad assembly [for providing a force resisting compression generally at an increasing rate when progressively compressed, thereby providing a low initial resistance to compression, but a high ultimate resistance to compression in urging said first and second load bearing members away from one another in response to a load being imposed upon at least one of said first and second abutment surfaces].

DO NOT ENTER

DO NOT ENTERREJECTION – §102(B) CARLSTONClaim 15

15. (Five Times Amended) A bearing pad assembly comprising:
a first housing having a bore extending through said first housing;
a first load bearing member coupled to said first housing and defining
an abutment surface opposite to said first housing;
a second housing having a bore extending through said second
housing, adapted to telescopically receive said first housing;
a second load bearing member coupled to said second housing and
defining an abutment surface opposite to said second housing; and
at least one compression spring in the shape of a [torus]toroid
positioned within said first housing bore, the toroid having an outside
diameter minus an inside diameter equal to or greater than a height when
positioned in the bearing pad assembly], for providing a force resisting
compression generally at an increasing rate when progressively compressed,
thereby providing a low initial resistance to compression, but a high ultimate
resistance to compression in urging said first and second abutment surfaces
away from each other in response to a load imposed on at least one of said
abutment surfaces].

DO NOT ENTER